

EPOCH BINOCULARS



| | XZ815 | X105** | X85** | X75 | XC10 | XC8 |
|-----------------------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|
| Power | 8-15X | 10.5X | 8.5X | 7.5X | 10X | 8X |
| Objective diameter | 35 mm | 43 mm | 43 mm | 43 mm | 25 mm | 21 mm |
| Overall dimensions | 6"x5.2"x2.2" | 5.8"x5"x2" | 5.8"x5"x2" | 6"x5"x2" | 4.3"x4.8"x1.5" | 4.3"x4"x1.5" |
| Weight | 32 oz | 25 oz | 25 oz | 26 oz | 13.5 oz | 13 oz |
| Frame material | Mg Alloy | Mg Alloy | Mg Alloy | Mg Alloy | Mg Alloy | Mg Alloy |
| Close focus distance | 6 ft | 3 ft | 3 ft | 3 ft | 9 ft | 6 ft |
| Exit pupil | 4.4 mm* | 4.1 mm | 5.1 mm | 5.7 mm | 2.5 mm | 2.6 mm |
| Eye relief**** | 17 mm | 17 mm | 19.5 mm | 20 mm | 15 mm | 15 mm |
| Twist up eye relief type | Locking multi-step | Locking multi-step | Locking multi-step | Locking multi-step | Locking multi-step | Locking multi-step |
| Field of view at 1000 yds | 273 ft* | 290 ft | 315 ft | 370 ft | 314 ft | 393 ft |
| Aspheric ocular lenses | Yes | Yes | Yes | Yes | Yes | Yes |
| Prism type | SF | SF | SF | SF | SF | SF |
| Phase coating | Yes | Yes | Yes | Yes | Yes | Yes |
| Prism coating | AL-HR | AL-HR | AL-HR | AL-HR | AL-HR | AL-HR |
| Lens coating type | Flat Light | Flat Light | Flat Light | Flat Light | Flat Light | Flat Light |
| Locking diopter adjustment | Yes | Yes | Yes | Yes | Yes | Yes |
| Waterproof / fogproof | Yes | Yes | Yes | Yes | Yes | Yes |
| Nitrogen filled | Yes | Yes | Yes | Yes | Yes | Yes |
| Tripod compatible | Yes | Yes | Yes | Yes | No | No |
| Warranty type | HALO Lifetime | HALO Lifetime | HALO Lifetime | HALO Lifetime | HALO Lifetime | HALO Lifetime |

FEATURES

* At lowest power

** Also available in Mossy Oak® Break-Up™

*** Also available in marine yellow

**** In general, optics with at least 15mm of eye relief are considered eyeglass compatible