

ETERNA BINOCULARS



	E1551	E1145***	E845	E1032	E832	E1025	E825
Power	15X	11X	8X	10X	8X	10X	8X
Objective diameter	51 mm	45 mm	45 mm	32 mm	32 mm	25 mm	25 mm
Overall dimensions	6.7"x5.2"x2.3"	6"x5.1"x2.2"	6"x5.1"x2.2"	5.4"x4.8"x2"	5.4"x4.8"x2"	4.8"x3.8"x1.8"	4.8"x3.8"x1.8"
Weight	32 oz	28 oz	28 oz	25 oz	25 oz	12 oz	12 oz
Frame material	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum
Close focus distance	11 ft	8 ft	8 ft	4 ft	4 ft	9 ft	6 ft
Exit pupil	3.4 mm	4.1 mm	5.6 mm	3.2 mm	4 mm	2.5 mm	3.1 mm
Eye relief****	15 mm	19.5 mm	20 mm	15 mm	16 mm	17 mm	18.5 mm
Twist up eye relief type	Multi-step	Multi-step	Multi-step	Multi-step	Multi-step	Multi-step	Multi-step
Field of view at 1000 yds	200 ft	305 ft	315 ft	315 ft	394 ft	260 ft	270 ft
Aspheric ocular lenses	No	No	No	No	No	No	No
Prism type	BaK-4	BaK-4	BaK-4	BaK-4	BaK-4	BaK-4	BaK-4
Phase coating	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Prism coating	AL	AL	AL	AL	AL	AL	AL
Lens coating type	Full multi	Full multi	Full multi	Full multi	Full multi	Full multi	Full multi
Locking diopter adjustment	No	No	No	No	No	No	No
Waterproof / fogproof	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Nitrogen filled	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Tripod compatible	Yes	Yes	Yes	Yes	Yes	No	No
Warranty type	Limited lifetime	Limited lifetime	Limited lifetime	Limited lifetime	Limited lifetime	Limited lifetime	Limited lifetime

FEATURES

* At lowest power

** Also available in Mossy Oak® Break-Up™

*** Also available in marine yellow

**** In general, optics with at least 15mm of eye relief are considered eyeglass compatible