

## SCOPES



### SPOTTING SCOPES

### MONOCULARS

9080EDW-A	9080EDW-S	9050ED-S	E630	7040-MACRO	7018
-----------	-----------	----------	------	------------	------

### FEATURES

	20-60X	20-60X	18-38X	6X	7X	7X
Power	20-60X	20-60X	18-38X	6X	7X	7X
Objective diameter	80 mm	80 mm	50 mm	30 mm	40 mm	18 mm
Overall dimensions	15.5"x3.6"x4.3"	15.5"x3.6"x4.3"	8.1"x4"x4"	6"x2"x1.9"	6.5"x2.6"x2.5"	1.3"x3.3"
Weight	3.5 lbs	3.5 lbs	24 oz	11.5 oz	11.3 oz	1.8 oz
Frame material	Aluminum	Aluminum	Aluminum	Polymer	Polymer	Polymer
Close focus distance	20 ft*	20 ft*	20 ft*	12 ft	1.5 ft	1.1 ft
Exit pupil	4 mm*	4 mm*	2.8 mm*	5 mm	5.7 mm	2.6 mm
Eye relief****	17 mm	17 mm	16 mm	19 mm	15 mm	12 mm
Twist up eye relief type	Multi-step	Multi-step	Multi-step	--	Standard	--
Field of view at 1000 yds	98 ft*	98 ft*	141 ft*	341 ft	336 ft	181 ft
Aspheric ocular lenses	No	No	No	No	No	No
Prism type	BaK-4	BaK-4	BaK-4	BaK-4	BaK-4	BaK-4
ED Glass	Yes	Yes	Yes	No	No	No
Lens coating type	Full multi	Full multi	Full multi	Full multi	Full multi	Multi
Waterproof / fogproof	Yes	Yes	Yes	Yes	No	No
Nitrogen filled	Yes	Yes	Yes	Yes	No	No
Tripod compatible	Yes	Yes	Yes	No	Yes	No
Warranty type	Limited lifetime	Limited lifetime	Limited lifetime	Limited lifetime	One year	One year

\* At lowest power

\*\* Also available in Mossy Oak® Break-Up™

\*\*\* Also available in marine yellow

\*\*\*\* In general, optics with at least 15mm of eye relief are considered eyeglass compatible